

ENDURANCE GENERATORS

The EC models are the workhorses of our generator range. Their renowned endurance and minimal maintenance requirements make our robust EC the generator of choice for consumers, artisans and semi-professionals. Designed with core values of simple design, reliable starting and extreme durability, they provide raw power for the most heavy-duty applications, from the toughest environments to the harshest and most demanding emergency situations.

Powered by our easy-starting, commercial grade, 4-stroke GX engines, they are ultra-reliable thanks to our Oil Alert™ function that shuts down the engine if the oil level drops below a safe level, preventing costly damage. The engine and alternator are rubber mounted within a powder-coated tubular steel frame for reduced vibration, increased protection and easy lifting.

ENDURANCE GENERATORS POPULAR USES

- Construction equipment
- Hire companies
- Standard lighting
- Emergency services
- Industrial power tools



EC 2000

ECM 2800

EC 3600

EC 5000

ECT 7000

ECMT 7000*

ECT 7000P*

For feature and technology symbol glossary see page 10

For full generator model specifications see page 22

- Max output**
- Rated output
- Fuel tank capacity
- Operating time at rated load
- Dimensions (mm)
- Dry weight
- Sound power level (2000/14/EC, 2005/88/EC)
- Power output
- Socket output




2000W
1700W
3.3L
2h50
L 585 x W 435 x H 440
36kg
95dB(A)
Condenser
16A 230V / 16A 115V



2800W
2500W
14.2L
9h
L 645 x W 435 x H 490
50kg
96dB(A)
Condenser
16A 230V / 16A 115V



3600W
3400W
5.3L
3h
L 800 x W 550 x H 540
58kg
97dB(A)
Condenser
16A 230V / 16A 115V



5000W
4500W
6.2L
2h50
L 800 x W 550 x H 540
75kg
97dB(A)
Condenser
2 x 16A 230V / 1 x 16A 115V / 1 x 32A 115V



4000W / 7000W†
3600W / 6500W†
6.2L
2h15
L 800 x W 550 x H 540
77kg
97dB(A)
Inductive
16A 400V / 16A 230V



4000W / 7000W†
3600W / 6500W†
6.2L
8h10
L 755 x W 550 x H 560
104kg
97dB(A)
Inductive
16A 400V / 16A 230V



4000W / 7000W†
3600W / 5200W†
6.2L
2h15
L 800 x W 550 x H 540
86kg
97dB(A)
Inductive
16A 250V

*Not available in the UK. **Optional wheel kit available. † The 2 power values shown are for single-phase and three-phase output. Photography shown for model illustration only.